

VISIVART

DIGITAL SIGNAGE


New media, new life

VISIVART

Movable Signage

SP1000

2018-2019
datasheet / scheda tecnica



Panel Parameters <i>Parametri</i>	Resolution / Risoluzione	1366*768	1920*1080
	Screen Ratio / Formato	16: 9	
	Visual Angle / Angolo di visione	85/85/85/85	
	Refresh frequency / Aggiornamento frequenze	60Hz	60Hz
	Life Time / Durata	30000H	30000H
	Static contrast ratio / Contrasto	2400:1	1000:1
	Response speed / Velocità di risposta	6.5ms	12ms
	Max Brightness / Luminosità	300cd/m2	350cd/m2
Core Parameters <i>Parametri</i>	Chip	Dual core A53 processor\Quad core GPU\Dominant frequency: 1.2GHz	
	OS / Sistema operativo	Android 4.4.2	
	CPU / Processore	Dual core A53 processor / Processore Dual core A53	
	System memory / Memoria	1G DDR3	
	Hard disk storage / Disco rigido	8G	
Interface Setting <i>Interfaccia</i>	USB2.0	1	
	USB3.0	1	
	Earphone / Auricolare	0	
	LAN	0	
	TF Cassette / Alloggiamento Trans flesh	0	
	HDMI 2.0	0	
Basic functions <i>Funzioni base</i>	Horizontal and vertical display	/	/
	Timing switch / Timer integrato	yes / sì	yes / sì
	USB data input	yes / sì	yes / sì
	Cable network / Cavo di rete	no	no
	Wireless Wi-Fi	yes / sì	yes / sì
	Speaker Power / Altoparlanti	2*4W	2*4W
	Quantity of speaker / N. di altoparlanti	2	2
Interactive Device <i>Dispositivo interattivo</i>	Media Info Display / Display info	Support videos splitting, subtitle rolling, switch timing and USB data input / Supporto video, sottotitoli, timer e porta USB	
	Release System in Background (Option) / Aggiornamenti automatici	Support Program management/ Terminal management/ News making/ Program making -	
	Video Decoding / Formati video	3GP, 3G2, AVI,FLV,F4V,OGG,MP4,MOV,TS,M2TS,M2T,M2P,MKV.1920*1080 30Hz	
	Picture Format / Formato immagine	jpeg, png, gif, bmp.	
CBU Craft <i>Telaio</i>	CBU material / Materiale	Metal/ aluminum - Metallo / Alluminio	
	Frame material / Materiale cornice	Aluminum / Alluminio	
	CBU color / Colore	Black/white - Bianco/ Nero	Black/white - Bianco/Nero
	Frame Size / Dimensione cornice	25mm	35mm
	CBU Thickness / Spessore	30.3mm	36.3mm
	Distance Between Installing Holes	No	
	Quantity of Installing Holes	No	
Power Consumption <i>Consumi</i>	Rated Power Consumption / Consumi	45W	80W
	Standby Power Consumption / Consumi in standby	Less than 1W / Meno di 1W	
Structure Parameters <i>Dimensioni dispositivo</i>	CBU size(L*H*D) / Dimensioni	449*1334*30.3mm	587*1522*36.3mm
	Bracket thickness / Spessore	28.5mm	28.5mm
	Packaged Dimension (L*H*D) / Dimensioni confezione	1510*208*635mm	1703*212*762mm
	Net Weight (Kg) / Peso netto (kg)	16.34kg	25.27kg
	Gross Weight (Kg) / Peso lordo (Kg)	22.8kg	33.5kg
Max Stacking Layers / Livello max sovrapp.	4	3	
Loading Qty <i>Quantità per trasporto</i>	20GP/40GP/40HQ(SET)	117/249/332	99/210/210

DIGITAL SIGNAGE

VISIVART



Movable Signage

Totem Signage

Wall-Mount Signage